

GSR225



Trucks & Commercial Light Trucks, All Position



Regional




Urban | Light Duty

Regional Haul Steer and All Position Light Duty Tire




Features

Benefits



Four belt construction

Increases casing and tread stiffness, minimizing tire deformation for longer wear




Specially formulated tread compound

Improved tread wear resistance and handling characteristics



Resilient and proven four groove tread design

Provides consistent handling and vehicle control



Optimized sipe design on rib edges

Improved wet traction and minimized irregular wear



New, improved bead construction

Improved bead design for easier rim mounting

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs. @ PSI)	(Lbs. @ PSI)	Inch	Inch	Inch	32nds		Lbs.
225/70R19.5	100EV656Q	14	G	128/126 L	6.75	6.00	3,970@110	3,750@110	8.9	14.9	31.9	16	651	70
245/70R19.5	100EV2252Q	16	H	136/134 M	7.50	6.75	4,940@120	4,675@120	9.8	15.3	33.0	17	630	77
265/70R19.5	100EV1461Q	16	H	140/138 M	7.50	8.25	5,510@120	5,205@120	10.4	15.9	34.1	18	609	86
275/70R22.5	100EV2174Q	16	H	148/145 M (152/148 J)	8.25	9.00	6,945@130	6,395@130	10.9	17.5	37.7	19	551	111
315/80R22.5	100EV1980Q	20	L	158/150 L (154/150 M)	9.00	9.75	9,370@120	7,390@120	12.3	19.7	42.4	22	490	149

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.