

## **Regional Haul Steer Tire**

Features	Benefits
Special compound with low heat generation & longer wear	Provides higher tire mileage and improved fuel economy
Four groove design	Enhanced tread stiffness, reduce in rolling resistance, reliable control and handling
Multiple sipes on ribs	Optimum traction & braking
Optimized footprint distribution	Improves footprint performance to prevent irregular wear

Tire Size	Item Code	PR	LR		Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	I Danen	Overall Diameter	Tread Depth	- 1	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1782Q	14	G	144/142 L	8.25	7.5	6,175@105	5,840@105	11.0	19.3	41.5	21	501	132
11R22.5	100EV1991Q	16	Н	148/145 L	8.25	7.5	6,940@123	6,395@123	11.0	19.3	41.5	21	501	132
295/75R22.5	100EV1674Q	14	G	144/141 L	9.00	8.25	6,175@110	5,675@110	11.7	18.6	39.9	21	521	123

PR Ply Rating LR Load Range LI Load Index **SR** Speed Rating **RPM** Revolutions Per Mile