

Features	Benefits
Four straight groove design	Enhanced driving stability and effective water evacuation properties
Optimized footprint	Increased performance for wet grip
Continuous shoulder rib design	Provides excellent resistance to irregular wear
Special tread compound	Reduced rolling resistance and improved fuel economy

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius		Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1783Q	14	G	144/142 L	8.25	7.50	6,175@105	5,840@105	11.0	19.3	41.5	11	501	112
255/70R22.5	100EV1894Q	16	Н	140/137 L	7.50	8.25	5,510@120	5,070@120	10.0	17.1	36.6	11	568	89
295/75R22.5	100EV1191Q	14	G	144/141 L	9.00	8.25	6,175@110	5,675@110	11.7	18.6	39.9	11	521	104
11R24.5	100EV1448Q	14	G	146/143 L	8.25	7.50	6,610@105	6,005@105	11.0	20.3	43.5	11	478	121
285/75R24.5	100EV2120Q	14	G	144/141 L	8.25	_	6,175@110	5,675@110	11.1	19.4	41.3	11	503	110

PR Ply Rating LR Load Range

LI Load Index

SR Speed Rating

RPM Revolutions Per Mile

Giti manufactures SmartWay Verified Technologies. Learn more at epa.gov/smartway.

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.